

MILITARY SPECIFICATION

CAPACITOR, FIXED, ELECTROLYTIC (TANTALUM), CHIP,
ESTABLISHED RELIABILITY,

GENERAL SPECIFICATION FOR

This amendment forms a part of MIL-C-55365C, dated
23 August 1990, and is approved for use by all
Departments and Agencies of the Department of Defense.

PAGE 19

TABLE VII: Delete footnote 1/ and the reference thereto in its entirety.

PAGE 21

4.6.1.2.5.1, line 2: Delete "4.6.1.1" and substitute "4.6.1.1.1".

PAGE 22

4.6.1.3.1, line 2: Delete "2" and substitute "3".

4.6.1.3.1, line 5: Delete "month" and substitute "three-month period".

PAGE 23

TABLE X, Number of failures allowed column: Delete "1" for subgroup III and extend the bracket for 1 failure
allowed for subgroups I and II to include subgroup III.

CONCLUDING MATERIAL

Custodians:

Army - ER
Navy - EC
Air Force - 85

Preparing activity:

Army - ER

Agent:

DLA - ES

Review activities:

Army - MI
Navy - SH
Air Force - 17, 99
NASA - NA
DLA - ES

(Project 5910-1768)

User activities:

Army - AR
Navy - AS, CG, MC, OS
Air Force - 19